



Scaled Performance Table: S144

Catalog Number	Output	Length (feet)	# of LEDs	Lumens	Lumens per foot	Input Watts	Watts per foot	Efficacy	CCT	CRI
S144-L-2-*-**-L0*-927-00	Low	2FT	72	750	375	6	3.1	119	2700K	90
S144-L-2-*-**-L0*-930-00	Low	2FT	72	772	386	6	3.1	123	3000K	90
S144-L-2-*-**-L0*-935-00	Low	2FT	72	772	386	6	3.1	123	3500K	90
S144-L-2-*-**-L0*-940-00	Low	2FT	72	789	395	6	3.1	126	4000K	90
S144-S-2-*-**-L0*-927-00	Standard	2FT	72	1494	747	13	6.3	119	2700K	90
S144-S-2-*-**-L0*-930-00	Standard	2FT	72	1538	769	13	6.3	122	3000K	90
S144-S-2-*-**-L0*-935-00	Standard	2FT	72	1538	769	13	6.3	122	3500K	90
S144-S-2-*-**-L0*-940-00	Standard	2FT	72	1573	786	13	6.3	125	4000K	90
S144-H-2-*-**-L0*-927-00	High	2FT	72	2850	1425	26	13.0	110	2700K	90
S144-H-2-*-**-L0*-930-00	High	2FT	72	2934	1467	26	13.0	113	3000K	90
S144-H-2-*-**-L0*-935-00	High	2FT	72	2934	1467	26	13.0	113	3500K	90
S144-H-2-*-**-L0*-940-00	High	2FT	72	3001	1500	26	13.0	116	4000K	90
S144-L-3-*-**-L0*-927-00	Low	3FT	108	1125	375	9	3.1	119	2700K	90
S144-L-3-*-**-L0*-930-00	Low	3FT	108	1158	386	9	3.1	123	3000K	90
S144-L-3-*-**-L0*-935-00	Low	3FT	108	1158	386	9	3.1	123	3500K	90
S144-L-3-*-**-L0*-940-00	Low	3FT	108	1184	395	9	3.1	126	4000K	90
S144-S-3-*-**-L0*-927-00	Standard	3FT	108	2241	747	19	6.3	119	2700K	90
S144-S-3-*-**-L0*-930-00	Standard	3FT	108	2307	769	19	6.3	122	3000K	90
S144-S-3-*-**-L0*-935-00	Standard	3FT	108	2307	769	19	6.3	122	3500K	90
S144-S-3-*-**-L0*-940-00	Standard	3FT	108	2359	786	19	6.3	125	4000K	90
S144-H-3-*-**-L0*-927-00	High	3FT	108	4275	1425	39	13.0	110	2700K	90
S144-H-3-*-**-L0*-930-00	High	3FT	108	4400	1467	39	13.0	113	3000K	90
S144-H-3-*-**-L0*-935-00	High	3FT	108	4400	1467	39	13.0	113	3500K	90
S144-H-3-*-**-L0*-940-00	High	3FT	108	4501	1500	39	13.0	116	4000K	90
S144-L-4-*-**-L0*-927-00	Low	4FT	144	1499	375	13	3.1	119	2700K	90
S144-L-4-*-**-L0*-930-00	Low	4FT	144	1544	386	13	3.1	123	3000K	90
S144-L-4-*-**-L0*-935-00	Low	4FT	144	1544	386	13	3.1	123	3500K	90
S144-L-4-*-**-L0*-940-00	Low	4FT	144	1579	395	13	3.1	126	4000K	90
S144-S-4-*-**-L0*-927-00	Standard	4FT	144	2988	747	25	6.3	119	2700K	90
S144-S-4-*-**-L0*-930-00	Standard	4FT	144	3076	769	25	6.3	122	3000K	90
S144-S-4-*-**-L0*-935-00	Standard	4FT	144	3076	769	25	6.3	122	3500K	90
S144-S-4-*-**-L0*-940-00	Standard	4FT	144	3146	786	25	6.3	125	4000K	90
S144-H-4-*-**-L0*-927-00	High	4FT	144	5699	1425	52	13.0	110	2700K	90
S144-H-4-*-**-L0*-930-00	High	4FT	144	5867	1467	52	13.0	113	3000K	90
S144-H-4-*-**-L0*-935-00	High	4FT	144	5867	1467	52	13.0	113	3500K	90
S144-H-4-*-**-L0*-940-00	High	4FT	144	6002	1500	52	13.0	116	4000K	90

Scaled Performance Table: S144

Catalog Number	Output	Length (feet)	# of LEDs	Lumens	Lumens per foot	Input Watts	Watts per foot	Efficacy	CCT	CRI
S144-L-5-*-**-L0*-927-00	Low	5FT	180	1874	375	16	3.1	119	2700K	90
S144-L-5-*-**-L0*-930-00	Low	5FT	180	1929	386	16	3.1	123	3000K	90
S144-L-5-*-**-L0*-935-00	Low	5FT	180	1929	386	16	3.1	123	3500K	90
S144-L-5-*-**-L0*-940-00	Low	5FT	180	1974	395	16	3.1	126	4000K	90
S144-S-5-*-**-L0*-927-00	Standard	5FT	180	3735	747	31	6.3	119	2700K	90
S144-S-5-*-**-L0*-930-00	Standard	5FT	180	3845	769	31	6.3	122	3000K	90
S144-S-5-*-**-L0*-935-00	Standard	5FT	180	3845	769	31	6.3	122	3500K	90
S144-S-5-*-**-L0*-940-00	Standard	5FT	180	3932	786	31	6.3	125	4000K	90
S144-H-5-*-**-L0*-927-00	High	5FT	180	7124	1425	65	13.0	110	2700K	90
S144-H-5-*-**-L0*-930-00	High	5FT	180	7334	1467	65	13.0	113	3000K	90
S144-H-5-*-**-L0*-935-00	High	5FT	180	7334	1467	65	13.0	113	3500K	90
S144-H-5-*-**-L0*-940-00	High	5FT	180	7502	1500	65	13.0	116	4000K	90
S144-L-6-*-**-L0*-927-00	Low	6FT	216	2249	375	19	3.1	119	2700K	90
S144-L-6-*-**-L0*-930-00	Low	6FT	216	2315	386	19	3.1	123	3000K	90
S144-L-6-*-**-L0*-935-00	Low	6FT	216	2315	386	19	3.1	123	3500K	90
S144-L-6-*-**-L0*-940-00	Low	6FT	216	2368	395	19	3.1	126	4000K	90
S144-S-6-*-**-L0*-927-00	Standard	6FT	216	4482	747	38	6.3	119	2700K	90
S144-S-6-*-**-L0*-930-00	Standard	6FT	216	4614	769	38	6.3	122	3000K	90
S144-S-6-*-**-L0*-935-00	Standard	6FT	216	4614	769	38	6.3	122	3500K	90
S144-S-6-*-**-L0*-940-00	Standard	6FT	216	4719	786	38	6.3	125	4000K	90
S144-H-6-*-**-L0*-927-00	High	6FT	216	8549	1425	78	13.0	110	2700K	90
S144-H-6-*-**-L0*-930-00	High	6FT	216	8801	1467	78	13.0	113	3000K	90
S144-H-6-*-**-L0*-935-00	High	6FT	216	8801	1467	78	13.0	113	3500K	90
S144-H-6-*-**-L0*-940-00	High	6FT	216	9002	1500	78	13.0	116	4000K	90
S144-L-7-*-**-L0*-927-00	Low	7FT	252	2624	375	22	3.1	119	2700K	90
S144-L-7-*-**-L0*-930-00	Low	7FT	252	2701	386	22	3.1	123	3000K	90
S144-L-7-*-**-L0*-935-00	Low	7FT	252	2701	386	22	3.1	123	3500K	90
S144-L-7-*-**-L0*-940-00	Low	7FT	252	2763	395	22	3.1	126	4000K	90
S144-S-7-*-**-L0*-927-00	Standard	7FT	252	5229	747	44	6.3	119	2700K	90
S144-S-7-*-**-L0*-930-00	Standard	7FT	252	5383	769	44	6.3	122	3000K	90
S144-S-7-*-**-L0*-935-00	Standard	7FT	252	5383	769	44	6.3	122	3500K	90
S144-S-7-*-**-L0*-940-00	Standard	7FT	252	5505	786	44	6.3	125	4000K	90
S144-H-7-*-**-L0*-927-00	High	7FT	252	9974	1425	91	13.0	110	2700K	90
S144-H-7-*-**-L0*-930-00	High	7FT	252	10268	1467	91	13.0	113	3000K	90
S144-H-7-*-**-L0*-935-00	High	7FT	252	10268	1467	91	13.0	113	3500K	90
S144-H-7-*-**-L0*-940-00	High	7FT	252	10503	1500	91	13.0	116	4000K	90



Scaled Performance Table: S144

Catalog Number	Output	Length (feet)	# of LEDs	Lumens	Lumens per foot	Input Watts	Watts per foot	Efficacy	CCT	CRI
S144-L-8-*-**-L0*-927-00	Low	8FT	288	2999	375	25	3.1	119	2700K	90
S144-L-8-*-**-L0*-930-00	Low	8FT	288	3087	386	25	3.1	123	3000K	90
S144-L-8-*-**-L0*-935-00	Low	8FT	288	3087	386	25	3.1	123	3500K	90
S144-L-8-*-**-L0*-940-00	Low	8FT	288	3158	395	25	3.1	126	4000K	90
S144-S-8-*-**-L0*-927-00	Standard	8FT	288	5976	747	50	6.3	119	2700K	90
S144-S-8-*-**-L0*-930-00	Standard	8FT	288	6153	769	50	6.3	122	3000K	90
S144-S-8-*-**-L0*-935-00	Standard	8FT	288	6153	769	50	6.3	122	3500K	90
S144-S-8-*-**-L0*-940-00	Standard	8FT	288	6292	786	50	6.3	125	4000K	90
S144-H-8-*-**-L0*-927-00	High	8FT	288	11399	1425	104	13.0	110	2700K	90
S144-H-8-*-**-L0*-930-00	High	8FT	288	11734	1467	104	13.0	113	3000K	90
S144-H-8-*-**-L0*-935-00	High	8FT	288	11734	1467	104	13.0	113	3500K	90
S144-H-8-*-**-L0*-940-00	High	8FT	288	12003	1500	104	13.0	116	4000K	90
S144-L-9-*-**-L0*-927-00	Low	9FT	324	3374	375	28	3.1	119	2700K	90
S144-L-9-*-**-L0*-930-00	Low	9FT	324	3473	386	28	3.1	123	3000K	90
S144-L-9-*-**-L0*-935-00	Low	9FT	324	3473	386	28	3.1	123	3500K	90
S144-L-9-*-**-L0*-940-00	Low	9FT	324	3552	395	28	3.1	126	4000K	90
S144-S-9-*-**-L0*-927-00	Standard	9FT	324	6723	747	57	6.3	119	2700K	90
S144-S-9-*-**-L0*-930-00	Standard	9FT	324	6922	769	57	6.3	122	3000K	90
S144-S-9-*-**-L0*-935-00	Standard	9FT	324	6922	769	57	6.3	122	3500K	90
S144-S-9-*-**-L0*-940-00	Standard	9FT	324	7078	786	57	6.3	125	4000K	90
S144-H-9-*-**-L0*-927-00	High	9FT	324	12824	1425	117	13.0	110	2700K	90
S144-H-9-*-**-L0*-930-00	High	9FT	324	13201	1467	117	13.0	113	3000K	90
S144-H-9-*-**-L0*-935-00	High	9FT	324	13201	1467	117	13.0	113	3500K	90
S144-H-9-*-**-L0*-940-00	High	9FT	324	13503	1500	117	13.0	116	4000K	90

