



# Scaled Performance Table: S151

Catalog Number	Output	Length (feet)	# of LEDs	Lumens	Lumens per foot	Input Watts	Watts per foot	Efficacy	CCT	CRI
S151-L-2-*-*-00*-930-00	Low	2FT	72	799	399	7	3.3	122	3000K	90
S151-L-2-*-*-00*-935-00	Low	2FT	72	799	399	7	3.3	122	3500K	90
S151-L-2-*-*-00*-940-00	Low	2FT	72	817	409	7	3.3	124	4000K	90
S151-S-2-*-*-00*-930-00	Standard	2FT	72	1592	796	13	6.7	119	3000K	90
S151-S-2-*-*-00*-935-00	Standard	2FT	72	1592	796	13	6.7	119	3500K	90
S151-S-2-*-*-00*-940-00	Standard	2FT	72	1628	814	13	6.7	122	4000K	90
S151-H-2-*-*-00*-930-00	High	2FT	72	3037	1518	28	13.8	110	3000K	90
S151-H-2-*-*-00*-935-00	High	2FT	72	3037	1518	28	13.8	110	3500K	90
S151-H-2-*-*-00*-940-00	High	2FT	72	3107	1553	28	13.8	113	4000K	90
S151-L-3-*-*-00*-930-00	Low	3FT	108	1198	399	10	3.3	122	3000K	90
S151-L-3-*-*-00*-935-00	Low	3FT	108	1198	399	10	3.3	122	3500K	90
S151-L-3-*-*-00*-940-00	Low	3FT	108	1226	409	10	3.3	124	4000K	90
S151-S-3-*-*-00*-930-00	Standard	3FT	108	2389	796	20	6.7	119	3000K	90
S151-S-3-*-*-00*-935-00	Standard	3FT	108	2389	796	20	6.7	119	3500K	90
S151-S-3-*-*-00*-940-00	Standard	3FT	108	2443	814	20	6.7	122	4000K	90
S151-H-3-*-*-00*-930-00	High	3FT	108	4555	1518	41	13.8	110	3000K	90
S151-H-3-*-*-00*-935-00	High	3FT	108	4555	1518	41	13.8	110	3500K	90
S151-H-3-*-*-00*-940-00	High	3FT	108	4660	1553	41	13.8	113	4000K	90
S151-L-4-*-*-00*-930-00	Low	4FT	144	1598	399	13	3.3	122	3000K	90
S151-L-4-*-*-00*-935-00	Low	4FT	144	1598	399	13	3.3	122	3500K	90
S151-L-4-*-*-00*-940-00	Low	4FT	144	1634	409	13	3.3	124	4000K	90
S151-S-4-*-*-00*-930-00	Standard	4FT	144	3185	796	27	6.7	119	3000K	90
S151-S-4-*-*-00*-935-00	Standard	4FT	144	3185	796	27	6.7	119	3500K	90
S151-S-4-*-*-00*-940-00	Standard	4FT	144	3257	814	27	6.7	122	4000K	90
S151-H-4-*-*-00*-930-00	High	4FT	144	6074	1518	55	13.8	110	3000K	90
S151-H-4-*-*-00*-935-00	High	4FT	144	6074	1518	55	13.8	110	3500K	90
S151-H-4-*-*-00*-940-00	High	4FT	144	6213	1553	55	13.8	113	4000K	90
S151-L-5-*-*-00*-930-00	Low	5FT	180	1997	399	16	3.3	122	3000K	90
S151-L-5-*-*-00*-935-00	Low	5FT	180	1997	399	16	3.3	122	3500K	90
S151-L-5-*-*-00*-940-00	Low	5FT	180	2043	409	16	3.3	124	4000K	90
S151-S-5-*-*-00*-930-00	Standard	5FT	180	3981	796	33	6.7	119	3000K	90
S151-S-5-*-*-00*-935-00	Standard	5FT	180	3981	796	33	6.7	119	3500K	90
S151-S-5-*-*-00*-940-00	Standard	5FT	180	4071	814	33	6.7	122	4000K	90
S151-H-5-*-*-00*-930-00	High	5FT	180	7592	1518	69	13.8	110	3000K	90
S151-H-5-*-*-00*-935-00	High	5FT	180	7592	1518	69	13.8	110	3500K	90
S151-H-5-*-*-00*-940-00	High	5FT	180	7766	1553	69	13.8	113	4000K	90
S151-L-6-*-*-00*-930-00	Low	6FT	216	2397	399	20	3.3	122	3000K	90
S151-L-6-*-*-00*-935-00	Low	6FT	216	2397	399	20	3.3	122	3500K	90
S151-L-6-*-*-00*-940-00	Low	6FT	216	2452	409	20	3.3	124	4000K	90
S151-S-6-*-*-00*-930-00	Standard	6FT	216	4777	796	40	6.7	119	3000K	90
S151-S-6-*-*-00*-935-00	Standard	6FT	216	4777	796	40	6.7	119	3500K	90
S151-S-6-*-*-00*-940-00	Standard	6FT	216	4885	814	40	6.7	122	4000K	90
S151-H-6-*-*-00*-930-00	High	6FT	216	9111	1518	83	13.8	110	3000K	90
S151-H-6-*-*-00*-935-00	High	6FT	216	9111	1518	83	13.8	110	3500K	90
S151-H-6-*-*-00*-940-00	High	6FT	216	9320	1553	83	13.8	113	4000K	90